



Opaljet Supreme 5W30

PCMO, High Tech

FULL SYNTHETIC

U110007

9/2/2025

V 25.4

Low Sulphur engine oil ACEA C1 SAE 5W30

DESCRIPTION

OPALJET SUPREME is a top of the range oil providing the perfect protection of petrol or Diesel engines, turbo or not, equipped with injection pump or not and of their after-treatment (especially DPF).

The formulation is based on the "low saps" technology, that is to say very low content of sulphur, phosphor and sulfated ashes.

ADVANTAGES

OPALJET SUPREME ensures particles filters protection against clogging through the very low content of sulfur, phosphor and sulphated ash.

OPALJET SUPREME has low volatility and is unshearable thanks to its 100% synthetic nature.

The SAE 5W30 grade provides good lubrication without causing any significant energy loss.

SPECIFICATIONS

ACEA: C1-16, **API:** ,

NORMS / APPROVALS: SAE J300

SPECIFICATIONS: Ford WSS M2C 913-B, Ford WSS M2C 913-C, Ford WSS M2C934-B, JASO DL-1, Renault RN 720, Jaguar STJLR 03.5005

RECOMMENDATIONS:

AVAILABILITY

U110007	Bulk	IBC	Barrel	60L/53kg	20L steel	20L/ 18 kg plastic	4X5L	12X1L Specials	small / 400 gr
	/99	/97	/68	/42	/41	/29	/7	/12	

Opaljet Supreme 5W30

TECHNICAL DATA

-----E110007

PROPERTIES	UNIT	METHOD	VALUE
ACEA	Association Constructeurs Européennes de l'Automobile		C1-16
API	American Petroleum institute		
SAE / ISO-VG / NLGI			5W-30
COLOUR	Visual		
Density @ 15°C	kg / L	ASTM D1298	0.848
Pourpoint	°C	ASTM D97	-40
Flashpoint COC	°C	ASTM D92	226
Cinematic Viscosity @40°C	cSt	ASTM D7279	55
Kinematic viscosity @ 100°C	cSt	ASTM D7279	10
(V.I.) Viscosity index		ASTM D2270	171
Copper Corrosion		ASTM D130	
Anilinepoint	°C	ASTM D611	
Noack evap	% w/w	ASTM D 5800	12.5
CCS (cold crank)	cP @ -30°C	ASTM D 5293	6500
TBN	mg KOH/g	ASTM D 2896B	6.5
Sulphated Ash	% weight		0.5

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.