

OPALJET LONGLIFE PLUS

100% SYNTHETIC OIL FOR
LONGER DRAIN PERIODS

110009/01.18

Rev. 4

DESCRIPTION & APPLICATIONS

OPALJET LONGLIFE PLUS is an oil which responds to the most severe requirements of modern car engines, in all kind of services

OPALJET LONGLIFE PLUS guaranties perfect protection, extends the long life of all high performance parts (petrol, Diesel, turbo or multi-valved) and their after-treatment (especially DPF)

ADVANTAGES

- OPALJET LONGLIFE PLUS protects your engine when starting from extreme cold (-30°C) and allows a significant fuel economy compared to the use of a 15W40 grade.
- OPALJET LONGLIFE PLUS offers the reliable guarantee of fomulation constancy: the international seal ACEA C2/C3 and MB 229.5 / 229.31/229.51

PERFORMANCES

Satisfies to the following specifications:

ACEA C2-12/C3-12

API SN

BMW Longlife 04

DEXOS 2

FIAT 9.55535-S2

Ford M2C 917A

MB 229.31

PORSCHE A 40

RENAULT RN0700/RN0710

VW 502.00/505.00/505.01

OPALJET LONGLIFE PLUS

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	5W40
Specific gravity at 15°C	kg/m ³	NFT 60101	854
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	85
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	13,7
Viscosity index	-	NFT 60136	167
Dynamic viscosity at -30°C	mPa.s	ASTM D 5293	5950
Flash point	°C	NFT 60118	230
Pour point	°C	NFT 60105	-39
Sulphated ash content	% wheight	NF T 60143	0,78
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	7,2

The average values are given for information only.