

2T SPECIAL

2 STROKE ENGINE-OIL WITH SYNTHETIC COMPONENTS

110037-110038/04.15

Rev. 2

DESCRIPTION & APPLICATIONS

2 T SPECIAL is specially recommended for all 2 stroke aircooled engines working at very high temperatures.

2T SPECIAL can be used in all types gasolines.

Treat level : from 2 % and above, according to manufacturers recommendations. Add oil to petrol and not the other way round.

ADVANTAGES

- Large thermal stability, preventing against piston blocking.
- Excellent resistance to oxidation, preventing piston varnish.
- High detergency, for engine cleanliness.
- Very low sulfated ash level, for the prevention of preignition, exhaust port blocking and catalyst ompatibility in service.

PERFORMANCES

Satisfies to the following specifications:

API TC

JASO FC

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

2T SPECIAL

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Color	-	-	red
Specific gravity at 15°C	kg/m ³	NFT 60101	903
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	115
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	11,8
Flash point	°C	NFT 60118	238
Pour point	°C	NFT 60105	-21
Sulphated ash content	% wheight	NF T 60143	0,05
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	1,3
Product number	-	-	110037
Product number	100 ml	-	110038

The average values are given for information only.