

Multi S 5W40

Multi S 5W40 for all-round use

110061/03.18

Rev. 0

DESCRIPTION & APPLICATIONS

Multi S 5W40 is a motor oil specially adapted for lubricating both gasoline and diesel vehicles. (without DPF)

A fast lubrication at cold start, a perfect performance at high temperatures, an ideal lubricating film due to the good thermal stability and oxidation resistance guarantee reduced wear and longer engine life.

ADVANTAGES

- Allround product where a good 5W40 is required.
- Diesel and gasoline
- High performance engines with turbo, bi-turbo or compressor
- Engines under continuous heavy loads

PERFORMANCES

Satisfies to the following specifications:

ACEA A3/B4-12

API CF/SL

MB 229.1

RN 0700

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

Multi S 5W40

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	5W40
Specific gravity at 15°C	kg/m ³	NFT 60101	857
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	90
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	15
Viscosity index	-	NFT 60136	176
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	10,5

The average values are given for information only.