



Ignition 4T 10W40

PCMO, 4-T

FULL SYNTHETIC

U110504

9/2/2025

V 25.4

4T Motorcycle oil SAE 10W40 JASO MA-2

DESCRIPTION

This oil has been specially developed for the lubrication of four-stroke motorcycles, to prevent slipping, sticking and/or...

rough shifting of the clutch plates are a thing of the past.

Ignition 4T 5W-50 has been developed and tested in close collaboration with the most important motorcycle manufacturers and has already proven its qualities in practice.

ADVANTAGES

- A high and stable viscosity index.
- Optimal friction properties.
- Strong anti-wear, anti-corrosion and anti-foam properties.
- Very good detergent and dispersing effect.

SPECIFICATIONS

ACEA: -, **API:** SL,

NORMS / APPROVALS: 4T

SPECIFICATIONS: JASO MA, JASO MA-2, JASO T 903-2023

RECOMMENDATIONS: Motorcycle and Quad-like vehicles

AVAILABILITY

U110504	Bulk	IBC	Barrel	60L/53kg	20L steel	20L/ 18 kg plastic	4X5L	12X1L Specials	small / 400 gr
		/97	/68	/42			/7	/12	

Ignition 4T 10W40

TECHNICAL DATA

-----E110504

PROPERTIES	UNIT	METHOD	VALUE
ACEA	Association Constructeurs Européennes de l'Automobile		-
API	American Petroleum institute		SL
SAE / ISO-VG / NLGI			10W-40
COLOUR	Visual		
Density @ 15°C	kg / L	ASTM D1298	0.846
Pourpoint	°C	ASTM D97	-45
Flashpoint COC	°C	ASTM D92	236
Cinematic Viscosity @40°C	cSt	ASTM D7279	91
Kinematic viscosity @ 100°C	cSt	ASTM D7279	14
(V.I.) Viscosity index		ASTM D2270	165
Copper Corrosion		ASTM D130	
Anilinepoint	°C	ASTM D611	
Noack evap	% w/w	ASTM D 5800	12.6
TBN	mg KOH/g	ASTM D 2896B	7.7
Sulphated Ash	% weight		0.94

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.