

# IGNITION 4T 5W50

Synthetic four-stroke motorcycle oil.

110505/02.19

Rev. 0

## **DESCRIPTION & APPLICATIONS**

This oil is specially developed for the lubrication of four-stroke motorcycle engines, so that the slipping, sticking and / or rough shifting of the clutch plates is a thing of the past. This oil has been developed and tested in close cooperation with the most important motorcycle manufacturers and has already proven its qualities in practice.

## **ADVANTAGES**

- A high and stable viscosity index.
- Optimal friction properties.
- A strong anti-wear, anti-corrosion and anti-foam ability.
- A very good detergent and dispersing effect.

## **PERFORMANCES**

Satisfies to the following specifications:

API SL

JASO MA/MA2

## **ENVIRONMENT, HEALTH & SAFETY**

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

# IGNITION 4T 5W50

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Density at 15 °C	kg/l	ASTM D4052	0,847
Kinematic viscosity at 40°C	mm²/s.	ASTM D7279	110
Kinematic viscosity at 100°C	mm²/s.	ASTM D7279	17
Viscosity index	-	ASTM D2270	160
Flash point (COC)	°C	ASTM D 92	242
Pour point	°C	ASTM D7346	-24
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	7,7
Sulphated ash content	% wheight		0,94

*The average values are given for information only.*