

Opaljet 16 S

High quality 10W40 motor oil with synthetic components.

120026/11.23

Rev. 4

DESCRIPTION & APPLICATIONS

Opaljet 16S 10W40 is a motor oil with synthetic components. The oil is a perfect partner for slightly older cars, multi-purpose for both petrol and diesel engines. (diesel cars without exhaust aftertreatment systems). The high resistance to shear and low volatility (<15% in accordance with VW 505.00) at high temperatures will limit consumption to the lowest levels.

ADVANTAGES

- An extremely reliable oil for gasoline-and diesel engine cars (without DPF).
- Very good performance under all conditions (motorway driving, city traffic, heavy load of the engine ...)
- The perfect partner for mixed fleets with older engine technologies.

PERFORMANCES

Satisfies to the following specifications:

ACEA A3/B4-12/E2

API CF/SM

MAN 271

MB 228.1/229.1

MTU Category 1

RN 0700

VW 501.01/505.00

Volvo VDS

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

Opaljet 16 S

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	10W40
Density at 15°C	kg/m ³	NFT 60101	870
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	102
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	14,9
Viscosity index	-	NFT 60136	152
Dynamic viscosity at -25°C	mPa.s	ASTM D 5293	6500
Flash point	°C	NFT 60118	201
Pour point	°C	NFT 60105	-33
Noack evaporation loss	% weight	CEC-L-40-T-87	12,1
Sulphated ash content	% weight	NF T 60143	1,13
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	9,3

The average values are given for information only.