

OPALJET POWER 5W30

100% SYNTHETIC OIL FOR
LONGER DRAIN PERIODS

120028/01.24

Rev. 9

DESCRIPTION & APPLICATIONS

OPALJET POWER 5W30 is an oil which responds to the most severe requirements of modern car engines, in all kind of services.

OPALJETPOWER 5W30 guaranties perfect protection, extends the long life of all high performance parts (petrol, Diesel, turbo or multi-valved) and their after-treatment (especially DPF).

Approvals
Ford WSS-M2C-913D

ADVANTAGES

- OPALJET POWER protects your engine when starting from extreme cold (-30°C) and allows a significant fuel economy compared to the use of a 15W40 grade.
- OPALJET POWER offers the reliable guarantee of fomulation constancy: the international seal: ACEA A5/B5 and API SM/CF.

PERFORMANCES

Satisfies to the following specifications:

ACEA A5/B5-16
API SL/CF
CHRYSLER MS 11106
Ford WSS M2C913A/M2C913B/M2C913C/M2C913D
Jaguar STJLR 03.5003
MAZDA
RN 0700

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

OPALJET POWER 5W30

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	5W30
Density at 15°C	kg/m ³	NFT 60101	860
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	58
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	11
Viscosity index	-	NFT 60136	178
Dynamic viscosity at -30°C	mPa.s	ASTM D 5293	4350
Flash point	°C	NFT 60118	234
Pour point	°C	NFT 60105	-36
Noack evaporation loss	% weight	CEC-L-40-T-87	9,2
Sulphated ash content	% weight	NF T 60143	0,492
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	9,97

The average values are given for information only.