

# AGRIALLE 15W30

MULTIFUNCTIONAL LUBRICANT FOR AGRICULTURAL TRACTORS

120030/11.23

Rev. 11

## **DESCRIPTION & APPLICATIONS**

AGRIALLE, a STOU (Super Tractor Oil Universal) lubricant, is used for the lubrication of any mechanism of agricultural machines : tractors, combine harvesters.

This multifunctional lubricant is recommended because it allows a rationalisation of supply and therefore prevents against any risk of error.

## **ADVANTAGES**

- Multifunctional : engines, hydraulic, mechanical transmissions, wet brakes.
- Viscosity has been studied for an easy start at low temperatures and for a quick transmission of hydraulic control.
- Well-adapted to load which can be found on mechanical transmissions of these machines.

## **PERFORMANCES**

Satisfies to the following specifications:

ACEA E4-08/E7-08

ALLISON C4

API CE/CF-4/CG-4/CI-4/GL4/SF

CAT TO4

Ford M2C 159B

JD J20A/J20C/J20D/J27

MAN 271

MB 227.1/228.1/228.3

MF M1139/M1141/M1144/M1145

MIL-L-2104D

ZF-TE-ML 06B/06C/07B

# AGRIALLE 15W30

## ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	15W30
Density at 15°C	kg/m <sup>3</sup>	NFT 60101	890
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	79,4
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	NFT 60100	10,9
Viscosity index	-	NFT 60136	125
Viscosity CCS at -20°C	mPa.s	NFT 60152	6031
Flash point	°C	ISO 2719	234
Pour point	°C	NFT 60105	-33
Sulphated ash content	% weight	NF T 60143	1,5
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	12,7

*The average values are given for information only.*