

# AGRIALLE 15W40

Multifunctional 15W40 lubricant (S.T.O.U.) for agriculture

120035/02.24

Rev. 13

## **DESCRIPTION & APPLICATIONS**

Agrialle 15W40 is a multipurpose lubricant for farm tractors. It is a S.T.O.U. (Super Tractor Oil Universal) for optimal lubrication of all parts of agricultural equipment: tractors, harvesters, shredders, etc.

All engines, hydraulic systems, mechanical transmissions, wet brakes can be lubricated with Agrialle. The high-quality base oils and specific additives ensure good corrosion resistance, good anti-foam properties and good shear-resistance.

Your vehicle will always be optimally lubricated. Because of its broad field of application, Agrialle is also an ideal partner for the rationalization of your oil inventory, you prevent the use of an incorrect lubricant, and you can limit your inventory to a minimum.

## **ADVANTAGES**

- All-round applicable where a S.T.O.U. 15W40 is required.
- Ideal for mixed fleets.
- Ideal to rationalise your oil inventory.
- Perfectly applicable for heavy loads of mechanical transmissions.
- Good for preventing brake noises.
- The perfect motor oil when the OEM-homologation Massey Ferguson M1144 is required.

## **PERFORMANCES**

Satisfies to the following specifications:

ACEA E4-08/E7-08

ALLISON C4

API CE/CF-4/CG-4/CI-4/GL4

API GL5 (low speed, high torque)

CAT TO4

Ford M2C 159B

JD J20A/J20C/J20D/J27A

MAN 271

MB 227.1/228.1/228.3

MF M1139/M1141/M1144/M1145

MIL-L-2104D

ZF-TE-ML 06B/06C/07B

# AGRIALLE 15W40

## ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA	
SAE grade	-	-	15W40	
Density at 15°C	kg/m <sup>3</sup>	NFT 60101	890	
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	104	
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	NFT 60100	14,1	
Viscosity index	-	NFT 60136	138	
Viscosity CCS at -20°C	mPa.s	NFT 60152	6705	
Flash point	°C	NFT 60118	240	
Pour point	°C	NFT 60105	-33	
Sulphated ash content	% weight	NF T 60143	1,55	
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	12,7	
Product number	-	-	120035	

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA	
SAE grade	-	-	15W40	
Density at 15°C	kg/m <sup>3</sup>	NFT 60101	890	
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	104	
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	NFT 60100	14,1	
Viscosity index	-	NFT 60136	138	
Viscosity CCS at -20°C	mPa.s	NFT 60152	6705	
Flash point	°C	NFT 60118	240	
Pour point	°C	NFT 60105	-33	
Sulphated ash content	% weight	NF T 60143	1,55	
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	12,7	

*The average values are given for information only.*