

# OPALJET FEV

100% Synthetic engine oil with fuel saving properties

120079/01.24

Rev. 3

## **DESCRIPTION & APPLICATIONS**

Opaljet FEV 0W20 is a 100% synthetic engine oil which mainly finds its application in the latest fuel-saving engines.

The specific composition of Opaljet FEV makes it suitable for petrol and diesel engines from Volvo cars where a SAE 0W20 is required with VCC RBS0-2AE specification.

Opaljet FEV 0W20 also ensures a very smooth cold start at very low temperatures and a safe lubrication film at operating temperatures.

Approval

VCC RBS0-2AE

## **ADVANTAGES**

- Specifically applicable for the latest generation of engines where the focus is fuel economy.
- the 0W20 ACEA A1/B1 engine oil to be used for the newest EURO 6 engines.
- good resistance to "shearing"
- very good detergency properties
- A very strong protection against wear, corrosion and foaming

## **PERFORMANCES**

Satisfies to the following specifications:

ACEA C5-16

Volvo VCC RBS0-2AE

# OPALJET FEV

## ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	0W20
Density at 15°C	kg/m <sup>3</sup>	NFT 60101	843
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	45,90
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	NFT 60100	8,7
Viscosity index	-	NFT 60136	173
Flash point	°C	NFT 60118	220
Pour point	°C	NFT 60105	-45
Sulphated ash content	% weight	NF T 60143	0,8
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	7,7

*The average values are given for information only.*