

COMPRESSOR VR

LUBRICANT FOR ROTARY AIR COMPRESSORS

130009-130015-130018/11.13

Rev. 1

DESCRIPTION & APPLICATIONS

COMPRESSOR VR is specially recommended for the lubrication of screw rotary air compressors.

COMPRESSOR VR ISO VG 32, 46 or 68 are also suitable for vacuum pumps.

ADVANTAGES

- COMPRESSOR VR is formulated from paraffinic mineral oils selected for :
- Slight tendency to form deposits
- Exceptional resistance to oxidation
- Low volatility

PERFORMANCES

Satisfies to the following specifications:

ISO 6743 DAG/DAH

DIN 51506 VDL

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

COMPRESSOR VR

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA		
ISO VG	-	-	32	46	68
Specific gravity at 15°C	kg/m ³	NFT 60101	873	874	880
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	32,8	48	70
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	5,6	7,1	9
Viscosity index	-	NFT 60136	108	102	102
Flash point	°C	NFT 60118	222	230	240
Pour point	°C	NFT 60105	-30	-30	-24
Product number	-	-	130009	130015	

The average values are given for information only.