

# MATIC DX III

AUTOMATIC TRANSMISSION FLUID WITH DEXRON III-G LEVEL.

210038/01.24

Rev. 9

## **DESCRIPTION & APPLICATIONS**

Matic DX III is an ATF (Automatic Transmission Fluid), Dexron III-G.

This mineral based oil contains additives to provide excellent friction properties, a strong anti-oxidative ability (against cooler-corrosion), a perfect fluidity at very low temperatures and an unchanged behavior and quality at high temperatures.

Matic DX III is ideal for use in:

- automatic gearboxes
- power shift transmissions
- couplings and torque converters
- power steerings
- hydrostatic transmissions

Approvals

Voith Turbo H55.6335

ZF TE-ML 04D, 14A (Registration ZF001010)

## **ADVANTAGES**

- The ideal ATF where DEXRON III is required.
- Perfectly compatible with seals, ferrous and non-ferrous metals.
- Can also be used as hydraulic fluid, type HV, viscosity ISO VG 32.

# MATIC DX III

## PERFORMANCES

Satisfies to the following specifications:

ALLISON C4  
ALLISON TES 389  
CHRYSLER/DODGE/JEEP +/+2/+3  
Ford MERCON  
GM/GMC/OPEL/SATURN/DERON-IID /-III G  
MAN 339 type L-1  
MAN 339 type V1, Z1, Z2  
MAZDA ATF F- 1  
MB 236.1/236.5/236.6/236.7/236,9  
VOITH 55.6335  
VOLVO 97341  
ZF-TE ML 05L  
ZF-TE-ML 09/11A  
ZF-TE ML 14A  
ZF-TE-ML 11B  
ZF-TE ML 17C

## ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.  
When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

# MATIC DX III

## PROPERTIES

| CHARACTERISTICS              | UNITS                    | METHODS    | TYPICAL DATA |
|------------------------------|--------------------------|------------|--------------|
| Density at 15°C              | kg/m <sup>3</sup>        | NFT 60101  | 862          |
| Kinematic viscosity at 40°C  | mm <sup>2</sup> /s (cSt) | NFT 60100  | 35,8         |
| Kinematic viscosity at 100°C | mm <sup>2</sup> /s (cSt) | NFT 60100  | 8            |
| Viscosity index              | -                        | NFT 60136  | 200          |
| Dynamic viscosity at -40°C   | mPa.s                    | ASTM D2983 | 18000        |
| Flash point                  | °C                       | NFT 60118  | 176          |
| Pour point                   | °C                       | NFT 60105  | -48          |
| Colour / Saybolt             | -                        | ASTM D 156 | red          |
| Product number               | 208 L                    | -          | 210038       |

*The average values are given for information only.*