

GERION LS 75W140

100 % SYNTHETIC LUBRICANT FOR GEARBOXES AND FINAL DRIVES

210046/09.18

Rev. 2

DESCRIPTION & APPLICATIONS

GERION LS 75W140 is a lubricant specifically designed to lubricate the gearboxes and final drives of all private and industrial vehicles.

GERION LS 75W140 is specially recommended to lubricate self-locking or limited slip differentials fitted to industrial and off-road vehicles (4x4).

ADVANTAGES

- 100 % synthetic for exceptional product longevity
- Extreme-Pressure performance and reinforced anti-wear properties for effective resistance at very high loads.

PERFORMANCES

Satisfies to the following specifications:

API GL4/GL5-LS/MT-1

SAE J2360

MAN 341 Type E-3

MAN M 342 M3

SCANIA STO:01

MB 235.8

IVECO

DAF

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

GERION LS 75W140

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	75W140
Specific gravity at 15°C	kg/m ³	NFT 60101	901
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	180
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	24,5
Viscosity index	-	NFT 60136	165
Flash point	°C	NFT 60118	200
Dynamic viscosity at -40°C	mPa.s	ASTM D2983	<150000
Pour point	°C	NFT 60105	-40

The average values are given for information only.