

MATIC SEVEN

AUTOMATIC TRANSMISSION FLUID

210058/07.20

Rev. 10

DESCRIPTION & APPLICATIONS

MATIC SEVEN has been developed for the newest 7 and 8-step-automatic transmissions.

MATIC SEVEN improves fuel economy and ensures smoothly shifting gears.

MATIC SEVEN has improved friction characteristics which ensure excellent gear changing and smooth and flexible steering.

Caution: MATIC SEVEN oil does not replace previous DEXRON® standards (II D, III G, III H etc.).

MATIC SEVEN is particularly suitable for Mercedes Benz 7-speed transmission NAG-2 type.

Better fluidity at the lowest temperatures, ensuring an immediate lubrication, thanks to its high viscosity index

ADVANTAGES

- Thanks to its very high viscosity index. it has improved fluidity at the lowest temperatures and therefore ensures immediate lubrication during cold starts.
- Long life fluid thanks to the excellent resistance to oxidation
- Increased resistance to wear and oxidation.
- Good friction properties
- Increased transmission life.
- Strengthened anti-wear and oxidation power
- Compatible with elastomers.
- Protection against rust and corrosion.

MATIC SEVEN

PERFORMANCES

Satisfies to the following specifications:

AISIN WARNER AW-1
ATF M-1375.4
BMW/MINI ATF3/ATF3+
Chrysler ATF+4
DEXRON VI
GM/GMC/OPEL/SATURN AW1
HONDA DW-1
Hyundai SP IV
Hyundai SPH-IV
JAGUAR fluid 8432
JASO 1A
KIA SP-IV/SPH-IV
MASERATI P/N 231603
MAZDA ATF FZ/FW 6A EL/FW 6AX EL
MB 236.12/236.14/236.41
MERCON LV
MITSUBISHI ATF-J3
NISSAN MATIC S
ToYOTA JWS 3324
PORSCHE P/N 000 043 304 00
Shell L12108
TOYOTA WS
VW G 052 533
VW G 055 005/162/540
VW G 060 162
ZF 8HP/6HP-26

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

MATIC SEVEN

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Appearance	-	-	red
Specific gravity at 15°C	kg/m ³	NFT 60101	842
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	28,7
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	5,8
Viscosity index	-	NFT 60136	154
Dynamic viscosity at -40°C	mPa.s	ASTM D2983	9531
Flash point	°C	NFT 60118	216
Pour point	°C	NFT 60105	-48

The average values are given for information only.