

HYDRO NT 46

ZINC FREE HYDRAULIC OILS WITH
PERFORMANT CLEANING PROPERTIES

220115-220119/06.15

Rev. 0

DESCRIPTION & APPLICATIONS

HYDRO NT (New Technology) are hydraulic oils without zinc.

They are particularly indicated for the hydraulic systems with servovalves and proportional valves.

Their cleaning properties avoid carbon deposits at the hot points of the systems.

ADVANTAGES

- Strong cleaning properties.
- Excellent resistance to oxidation.
- Very high thermal stability.
- Antifoaming properties.
- Very good air release.
- Effective control of "stick-slip".

PERFORMANCES

Satisfies to the following specifications:

DIN 51502 HLP-D

DIN 51524 Teil 2 HLP

ISO 6743 HM

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

HYDRO NT 46

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA	
ISO VG	-	-	46	68
Specific gravity at 15°C	kg/m ³	NFT 60101	875	884
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	46	68
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	7	8,9
Viscosity index	-	NFT 60136	109	104
Flash point	°C	NFT 60118	222	227
Pour point	°C	NFT 60105	-21	-21
Rust preventing characteristics	-	DIN 51585	pass	pass
Copper corrosion	-	ASTM D 130	1a	1a

The average values are given for information only.