

MS 512

MINERAL PARAFFINIC OIL

230007/05.19

Rev. 3

DESCRIPTION & APPLICATIONS

The oils of the MS 500 series are highly refined paraffinic oils without extra additives, possessing a natural resistance to oxidation and belonging to ISO Class HH.

These lubricants are used for systems with lost lubrication, in not high loaded moderate severity transmissions.

Also suitable for vintage cars that undertake an oil type API SA.

ADVANTAGES

- Highly solvent refined oil.

PERFORMANCES

Satisfies to the following specifications:

ISO 6743 HH

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

MS 512

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
ISO VG	-	-	150
Specific gravity at 100°C	kg/m ³	NFT 60101	896
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	150
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	15
Viscosity index	-	NFT 60136	100
Flash point	°C	NFT 60118	271
Pour point	°C	NFT 60105	-12

The average values are given for information only.