

TRANSWAY HG

MULTIFUNCTIONAL OILS
FOR MACHINE TOOLS

230014-230015-230193-230195/05.22

Rev. 2

DESCRIPTION & APPLICATIONS

Oils for machine tools which have a central reservoir for the lubrication of the slideways as well as of the hydraulic system and some gearboxes.

Multifunctional

- Antiwear properties
- Anti stick-slip properties to prevent chattering
- Adhesively

ADVANTAGES

- Multifunctional.
- Antiwear properties.
- Anti stick-slip properties to prevent chattering.
- Adhesive properties.

PERFORMANCES

Satisfies to the following specifications:

CINCINNATI P50(ISO220)

DIN 51502 CGLP

ISO 6743-13 G

NFE 60200 HG

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

TRANSWAY HG

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA			
ISO VG	-	-	32	68	100	220
Density at 15°C	kg/m³	NFT 60101	872	879	885	892
Kinematic viscosity at 40°C	mm²/s (cSt)	NFT 60100	34	68	105	220
Kinematic viscosity at 100°C	mm²/s (cSt)	NFT 60100	6,4	8,8	11	18
Viscosity index	-	NFT 60136	100	102	93	95
Flash point	°C	NFT 60118	208	224	236	245
Pour point	°C	NFT 60105	-27	-24	-21	-21
TAN (TotalAcid Number)	mg KOH/g	ASTM D 664	0,97	0,97	0,97	0,97
Product number	-	-	230014	230015	230195	230193

The average values are given for information only.