

# AIRLUBE AA

## SPECIAL LUBRICATING OIL FOR PNEUMATIC OPERATED SYSTEMS

230107/05.17

Rev. 4

### DESCRIPTION & APPLICATIONS

AIRLUBE AA is intended for the lubrication of very sensitive pneumatic material, requiring the use of a fluid completely neutral towards the materials with which they interact.

AIRLUBE AA is particularly recommended for the lubrication of pneumatic equipment where the lubricant may come into incidental contact with food.

### ADVANTAGES

- Special additives give the AIRLUBE AA capacity to absorb up to 10% water (by weight) and to train its presence in a stable emulsion and lubricating and protecting the equipment against rust and corrosion.
- Prevents the formation of sludge and varnish and provide essential anti-wear.
- AIRLUBE AA is odorless and colorless.

### ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

### PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
NSF certificate number	-	-	133360
ISO VG	-	-	15
Kinematic viscosity at -40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	18
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	NFT 60100	4,3
Flash point	°C	NFT 60118	210
Pour point	°C	NFT 60105	-12

*The average values are given for information only.*