

GLISS GO-L-150

LUBRICANT FOR SLIDEWAYS OF VERTICAL LIFTS

230194/05.10

Rev. 0

DESCRIPTION & APPLICATIONS

GLISS GO-L 150 is recommended for the lubrication of movements under heavy load and high accuracy. This oil is been specifically formulated for slideways of vertical lifts.

ADVANTAGES

- GLISS GO have an excellent anti-stickslip effect thanks to their exceptional adhesiveness and extreme pressure properties.
- GLISS GO has perfect neutrality to coated and non coated slideways.
- GLISS GO-L is odorless.

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
ISO VG	-	-	150
Specific gravity at 15°C	kg/m ³	NFT 60101	890
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	155
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	15
Viscosity index	-	NFT 60136	95
Flash point	°C	NFT 60118	240
Pour point	°C	NFT 60105	-21

The average values are given for information only.