

# TEFLON +

TEFLON OILS

230500-230510/08.10

Rev. 0

## **DESCRIPTION & APPLICATIONS**

TEFLON + is a colloidal suspension in Teflon lubricant for maintenance of various material, both in the automotive industrial and wherever necessary lubrication of long duration, good penetration of the lubricant, good temperature resistance high and waterproof.

TEFLON + prevents rust and oxidation.

TEFLON + is used for the protection and lubrication of bearings, joints, cables, chains, guides, tools, firearms, etc. ...

TEFLON + is available in two viscosity (ISO VG 15 and 46) and is also available in spray as the PTFE +

Note: Teflon is a registered trademark of Dupont de Nemours.

## **ADVANTAGES**

- Prolonged lubrication, less maintenance.
- Very low friction coefficient.
- Lubrication at high temperature.
- Excellent penetration.
- Prevents corrosion.
- Frees bolts, screws and rusty nuts (penetrating effect)

## **ENVIRONMENT, HEALTH & SAFETY**

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

# TEFLON +

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA	
ISO VG	-	-	15	46
Specific gravity at 15°C	kg/m <sup>3</sup>	NFT 60101	862	874
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	15	46
Flash point	°C	NFT 60118	> 180	210
Pour point	°C	NFT 60105	-36	-33
4 Ball wear (1H, 40 Kg)	Ø mm	ASTM D2266	0,4	0,4
Product number	-	-	230510	230500

*The average values are given for information only.*