

Matic D

ATF oil with DEXRON II-D quality

263032/06.18

Rev. 2

DESCRIPTION & APPLICATIONS

Matic D is an ATF (Automatic Transmission Fluid) of the level Dexron II-D. This oil on mineral base has very good frictional properties and has a strong anti-oxidative ability which prevents cooler corrosion.

Matic D is ideal for use in:

- automatic gearboxes
- couplings and torque converters
- power steering systems
- hydrostatische transmissions
- hydraulic systems

ADVANTAGES

- The ideal ATF where DEXRON II-D is required.
- Fully compatible with gaskets
- Fully compatible with both ferrous and non-ferrous metals

PERFORMANCES

Satisfies to the following specifications:

ALLISON C4
Ford M2C 138 CJ
GM ATF DEXRON IID
GM ATF DEXRON II E
GM ATF TypeA Suffix A
MB 236,2
VOITH 55.6335
VOLVO 97340
ZF-TE ML 05L
ZF-TE-ML 09/21L

Matic D

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	kg/m ³	NFT 60101	881
Colour / Saybolt	-	ASTM D 156	red
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	40,8
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	8,1
Viscosity index	-	NFT 60136	178
Dynamic viscosity at -25°C	mPa.s	ASTM D 2602	2600
Dynamic viscosity at -40°C	mPa.s	ASTM D2983	38000
Flash point (PMCC)	°C	ASTM D 93	216
Pour point	°C	NFT 60105	-45
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	2

The average values are given for information only.