

# Fluid HIS 68 10W30

LUBRICANT FOR AGRICULTURAL TRACTORS  
HYDRAULICS, MECHANICAL TRANSMISSIONS, WET BRAKES

263045/01.16

Rev. 0

## DESCRIPTION & APPLICATIONS

FLUID HIS, a UTTO (Universal Tractor Transmission Oil) lubricant, can be used every time that a fluid is needed for the specifications listed below :

- Mechanical transmissions like gear boxes, converters and transfer boxes
- Hydraulic transmissions
- Wet brakes
- Hydraulic systems of certain fork lift trucks.
- All agricultural tractors with wet brakes like FIAT agricultural tractors.

FLUID HIS possesses all the properties to respond to the most severe requirements of multifunctional lubricants for agricultural tractors.

## ADVANTAGES

- Stability of oxidation : assures the maximum life expectancy in all the mechanisms where it is used
- Anti-wear and tear power and extreme pressure : assures lubrication without fault from gearing, pump, bearings and the hydraulic system.
- Anti-friction power : stops chattering and the noise of wet brakes.
- High viscosity index level : maintains a sufficient viscosity at high and low temperatures (SAE grade 10W30)
- Low freezing point : permits a good operation at very low temperatures
- Anti-corrosion protection : protects the pumps, gears, hydraulic system and brakes from corrosion and maintains their long life
- Excellent compatibility which avoids leakages
- Good filterability

# Fluid HIS 68 10W30

## PERFORMANCES

Satisfies to the following specifications:

AGCO POWERFLUID 821XL  
ALLISON C4  
API CG-4/GL4  
CAT TO2  
John Deere J20B/J20C/J20D  
Massey Ferguson CMS M 1135/1141/1143/1145  
Case New Holland CNH MAT 3505/3509/3525/3540  
CASE MS 1207/1210  
Ford ESN-M2C 86B/86C/134D  
FNHA-2-C-200.00  
FNHA-2-C-201.00  
Kubota UDT Fluid  
NH 410B  
VCE WB 101  
ZF-TE-ML 05F/03E/06K/17E/21F

## ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

# Fluid HIS 68 10W30

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	10W30
ISO VG	-	-	68
Specific gravity at 15°C	kg/m <sup>3</sup>	NFT 60101	878
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	63,3
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	NFT 60100	9,8
Viscosity index	-	NFT 60136	137
Dynamic viscosity at -35°C	mPa.s	ASTM D 5293	58000
Dynamic viscosity at -40°C	mPa.s	ASTM D2983	108000
Flash point	°C	NFT 60118	221
Pour point	°C	NFT 60105	-39
Sulphated ash content	% wheight	NF T 60143	1,16
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	7,1

*The average values are given for information only.*