

# Matic C4 10W

TRANSMISSION FLUID

263531/01.17

Rev. 0

## DESCRIPTION & APPLICATIONS

MATIC C 4 is a fluid specially elaborated for CATERPILLAR, it is also suitable for the lubrication of KOMATSU.

MATIC C4 SAE 10 W is used in hydraulic systems and hydrostatic transmissions.

## ADVANTAGES

- Excellent friction properties.
- Very good stability to oxidation.
- Good compatibility with elastomers.

## PERFORMANCES

Satisfies to the following specifications:

ALLISON C4

CAT TO4

CAT TO4 M

KOMATSU KES07.851/KES07.868.1

VICKERS M2950S

ZF-TE-ML 03D

## ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

# Matic C4 10W

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	10W
Specific gravity at 15°C	kg/m <sup>3</sup>	ISO 3675	881
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	38,7
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	NFT 60100	6,3
Viscosity index	-	NFT 60136	109
Flash point	°C	ISO 2719	218
Pour point	°C	ASTM D97	-36

*The average values are given for information only.*