

Matic C4 30

TRANSMISSION FLUID

263536/02.17

Rev. 6

DESCRIPTION & APPLICATIONS

MATIC C 4 is a fluid specially elaborated for CATERPILLAR, it is also suitable for the lubrication of KOMATSU.

MATIC C4 SAE 30 is particularly recommended in the friction mechanisms, such as:

- POWERSHIFT transmissions
- clutches
- brakes

ADVANTAGES

- Excellent friction properties.
- Very good stability to oxidation.
- Good compatibility with elastomeres.

PERFORMANCES

Satisfies to the following specifications:

ALLISON C4

CAT TO4

CAT TO4 M

KOMATSU KES07.851/KES07.868.1

VICKERS M2950S

ZF-TE-ML 03D

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

Matic C4 30

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	30
Specific gravity at 15°C	kg/m ³	NFT 60101	892
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	96
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	10,8
Viscosity index	-	NFT 60136	100
Flash point (COC)	°C	ASTM D 92	250
Pour point	°C	NFT 60105	-24

The average values are given for information only.