

Hydro HVI 68

MINERAL HYDRAULIC OILS ISO HV, WITH HIGH VISCOSITY INDEX

263585/02.17

Rev. 1

DESCRIPTION & APPLICATIONS

HYDRO HVI 68 is specially recommended for hydraulic systems operating at high pressure (higher than 350 bars), and for installations in which there are high temperature variations.

HYDRO HVI is essentially intended for applications requiring a high viscosity index fluid for general industrial, handling and civil engineering applications.

HYDRO HVI can also be applied in shock absorbers.

ADVANTAGES

- High shear stability, maintaining the initial viscosity
- High viscosity index
- Low pour point ensures excellent oil fluidity, even under very cold climate conditions.
- Excellent filtrability
- Hydrolysis resistance due to the stabilised zinc containing additive
- Oxidation resistance
- Thermal stability.

PERFORMANCES

Satisfies to the following specifications:

ISO 6743 HV/HV

DIN 51524 Teil 3 HVLP/HVLP

DENISON HF2/HF2

VICKERS M2950S/M2950S

VICKERS I 286S/286S

CINCINNATI P69(ISO68)/P69(ISO68)/P70(ISO46)/P70(ISO46)

US STEEL 127/127/136/136

NFE 48603 HV/HV

Hydro HVI 68

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
ISO VG	-	-	68
Specific gravity at 15°C	kg/m ³	NFT 60101	877
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	69
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	11
Viscosity index	-	NFT 60136	151
Dynamic viscosity at -10°C	mPa.s	ASTM D2602	2850
Flash point	°C	NFT 60118	224
Pour point	°C	NFT 60105	-33
Aniline Point	°C	NFM 07021	105
TAN (TotalAcid Number)	mg KOH/g	ASTM D 664	0,26

The average values are given for information only.