

Matic ATF

Lubricant for automatic transmissions

263630/11.17

Rev. 1

DESCRIPTION & APPLICATIONS

Matic ATF is an ATF (Automatic Transmission Fluid) level Dexron B. This oil on mineral base has very good frictional properties and has a strong anti-oxidative performance which prevents cooler corrosion.

Matic ATF is very suitable for use in:

- automatic gearboxes
- couplings and torque converters

ADVANTAGES

- Can be mixed with other fluids that comply with the standard GM ATF Type A Suffix A
- Also suitable for certain mechanical gearboxes (236.2 MB)
- An oil with a high oxidation stability, beneficial to the oil lifetime.

PERFORMANCES

Satisfies to the following specifications:

GM ATF TypeA Suffix A

MB 236,2

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

Matic ATF

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	kg/m ³	NFT 60101	870
Colour / Saybolt	-	ASTM D 156	red
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	37,8
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	7,3
Viscosity index	-	NFT 60136	164
Flash point	°C	NFT 60118	214
Pour point	°C	NFT 60105	-45
Product number	208 L	-	210030

The average values are given for information only.