



GREASE VA (12X1kg)

Grease, VASELINE

VASELINE

U310012

2/28/2025

V 25.2

Vaseline / Codex Pharma / NLGI 4 grease

DESCRIPTION

UNIL GREASE VA is a Vaseline grease that meets the European directives for various pharmacies, useful if the use of Vaseline is prescribed.

UNIL GREASE VA is particularly recommended for the lubrication of miscellaneous equipment that gets into contact with alimentary goods and equipment and pharmaceuticals where a grease is required.

ADVANTAGES

In accordance with Codex standards:

- XDE Edition (France)
- DAB 10 (Germany)
- BP 98 (United Kingdom)
- USP XXIII (USA)
- BP 98 (Grande-Bretagne)
- USP XXIII (Etats-Unis)

NORMS

/APPROVALS

Vaselin

SPECIFICATIONS

Codex

RECOMMENDATIONS

Droppoint 59°C

AVAILABILITY

	Bulk	IBC	Barrel	60L/53kg	20L steel	20L/ 18 kg plastic	4X5L	12X1L Specials	small / 400 gr
U310012				U310072				U310012	

GREASE VA (12X1kg)

TECHNICAL DATA

-----E310012

PROPERTIES	UNIT	METHOD	VALUE
ACEA	Association Constructeurs Européennes de l'Automobile		
API	American Petroleum institute		
SAE / ISO-VG / NLGI			NLGI 4
COLOUR	Visual		WHITE
Density @ 15°C	kg / L	ASTM D1298	
Pourpoint	°C	ASTM D97	
Flashpoint COC	°C	ASTM D92	
Cinematic Viscosity @40°C	cSt	ASTM D7279	
Kinematic viscosity @ 100°C	cSt	ASTM D7279	
(V.I.) Viscosity index		ASTM D2270	
Copper Corrosion		ASTM D130	
Anilinepoint	°C	ASTM D611	
Noack evap	% w/w	ASTM D 5800	
Sulphated Ash	% weight		
Smell / Geur / Odeur			none
Penetration 60 strokes @ 25°C	1/10mm	ASTM D 217	175-195

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.