

BIO A 500

ANTI-ADHESION AGENT
FOR ASPHALT

410127/01.10

Rev. 0

DESCRIPTION & APPLICATIONS

BIO A 500 is used to prevent asphalt from sticking to the surfaces of the trucks and containers.

BIO A 500 may also be applied in any application to prevent direct contact of hot asphalt with the surfaces of mixers or with any other materials.

It may also be added to the pulverisation systems of rolling lines in order to avoid sticking to the rollers.

EMPLOYMENT:

Store the concentrate above 4°C.

Use at 5% in water.

Preparation of the mixture: Add the concentrate to the water while mixing (never add water to the concentrate!)

To ease the mixing work, we can also offer automatic mixers.

ADVANTAGES

- BIO A 500 is used to prevent asphalt from sticking to the surfaces of the trucks and containers.
BIO A 500 may also be applied in any application to prevent direct contact of hot asphalt with the surfaces of mixers or with any other materials.
BIO A 500 may also be added to the pulverisation systems of rolling lines in order to avoid sticking to the rollers.
- Gain time for cleaning equipment
- Easy to use
- In addition to technical and economic advantages mentioned above, BIO A 500 is also biodegradable, and therefore a product that respects the environment.

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 1 year(s) in closed container and sheltered.

BIO A 500

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	kg/m ³	NFT 60101	920
Viscosity of the concentrate at 40°C	mm ² /s (cSt)	NFT 60100	46
pH at 5 % in water	-	-	8,3
Correction factor refractometer	coefficient	-	0,95

The average values are given for information only.