

KUTILUB DC 3 AM

MINERAL OILS FOR TURNING

410180-410185/02.24

Rev. 2

DESCRIPTION & APPLICATIONS

KUTILUB DC 3 is a clear mineral oil, specially developed for automatic turning of all types of steel. The forging and anti-wear additives as well as the absence of free sulfur allow this product to be used on all ferrous and non-ferrous metals, electrolytic copper, aluminum and duraluminium.

KUTILUB DC 3:

- ☐ - machining of hard steels
- ☐ - automatic turning and wire rolls of soft, semi-hard and hard languages
- ☐ - gear cutters with master milling of moderately hard steel and bronze.

-

ADVANTAGES

- The KUTILUB DC 3 is the ideal product for workshops that process different types of steel.
- Anti-fog property.

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Density at 15°C	kg/m ³	NFT 60101	898
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	32
Flash point	°C	NFT 60118	184
Pour point	°C	ASTM D97	-30

The average values are given for information only.