

MICROSPRAY MG AM

SPRAYABLE CUTTING OIL WITH LOW MIST PROPERTIES

410192/02.24 Rev. 1

DESCRIPTION & APPLICATIONS

Microspray MG AM is a sprayable, light colored cutting oil, containing anti-wear and lubricity additives, and is free of chlorine.

Microspray MG AM has been specially developed for all machining applications on non-ferrous metals.

It is also suitable for cutting, honing and profile grinding applications on a complete range of steels.

ADVANTAGES

- Does not stain copper and brass
- Its low viscosity and its wetting properties provide excellent cooling as well as high lubricity
- No oil mist, nor vapours.
- -

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

| CHARACTERISTICS | UNITS | METHODS | TYPICAL DATA |
|-----------------------------|-------------------|-----------|--------------|
| Density at 15°C | kg/m ³ | NFT 60101 | 878 |
| Kinematic viscosity at 40°C | mm²/s (cSt) | NFT 60100 | 9 |
| Flash point | °C | NFT 60118 | > 124 |

The average values are given for information only.