

SAFELUB RT 32 AM

FULL CUTTING OIL WITH EXTREMELY PRESS ADDITIVATION WITHOUT CHLORINE

410194/02.24

Rev. 1

DESCRIPTION & APPLICATIONS

SAFELUB RT 32 AM is a strongly additive cutting oil with an adapted viscosity for heavy operations (including roltrap operations, sawing operations, ...) on very hard metals, even metals containing up to 50% chromium.

-

ADVANTAGES

- Perfect surface finish.
- Provides extended service life (tool life) of the cutting tools.
- Good anti-fog properties.
- Workpiece easy to degrease due to emulsification,
- Good anti-corrosion properties.

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Density at 15°C	kg/m ³	NFT 60101	961
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	32
Flash point	°C	NFT 60118	165

The average values are given for information only.