

KUTILUB TF 9 (W)

NEAT CUTTING OIL FOR SEVERE MACHINING

410201-410364/02.24

Rev. 2

DESCRIPTION & APPLICATIONS

KUTILUB TF 9 (W) is an extremely strong cutting oil for tapping and threading of all kinds of steels

KUTILUB TF9 (W) is rincable with water, and it's multifunctionality makes it nice to have away from the workshop.

KUTILUB TF9 (W) has been especially developed for tapping and threading of all types of steels including high alloy and stainless steels.

ADVANTAGES

-
- Noticeably increase of the tool life.
- KUTILUB TF 9 W can be washed off with water
- * ..

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

| CHARACTERISTICS | UNITS | METHODS | TYPICAL DATA |
|-----------------------------|--------------------------|-----------|--------------|
| Density at 15°C | kg/m ³ | NFT 60101 | 995 |
| Kinematic viscosity at 40°C | mm ² /s (cSt) | NFT 60100 | 160 |
| Flash point | °C | NFT 60118 | > 200 |
| Color | - | - | rouge |

The average values are given for information only.