

KUTILUB FP 3 AM

MULTIFUNCTIONAL NEAT CUTTING OIL

410285/10.09

Rev. 0

DESCRIPTION & APPLICATIONS

KUTILUB FP 3 AM is a neat cutting oil of low viscosity and having extreme-pressure properties (EP).

Considering its multifunctional character, KUTILUB FP 3 AM is recommended for many difficult types of machining, where it is a primary importance to associate a good lubricity with a good cooling. It is suitable for all types of steels, including the stainless and high alloyed ones.

Examples of hard machining: deep drilling, gear cutting, tapping by watering, grinding with form wheel

ADVANTAGES

- By its fluidity and its wet ability, KUTILUB FP 3 AM provides an effective cooling.
- By its lubricity and cutting power, KUTILUB FP 3 AM increases the lifespan of the tools and makes it possible to obtain excellent surface finishing.
- Reinforced properties against mist forming.

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	kg/m ³	NFT 60101	904
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	14
Flash point	°C	NFT 60118	150
Product number	-	-	410285

The average values are given for information only.