

DEMOULSIL

MULTIPURPOSE SILICONE LUBRICANT

500004/10.10

Rev. 0

DESCRIPTION & APPLICATIONS

DEMOULSIL is a silicone oil diluted in a fluid and volatile agent. After evaporation of the agent is obtained on all types of materials a thin silicone film, uniform, without spots.

DEMOULSIL form a lubricating film that makes it virtually impossible to grip other substances. The field of applications is very diverse (sliding surfaces, chains, cables, hinges, locks, door seals, bushings, etc..). This product should not be applied when accidental contact with food or drinking water supply system is unavoidable.

It can also be used as release agent in the plastics industry.

ADVANTAGES

- Chemically inactive
- No aging under the influence of air and light.
- Excellent resistance to oxidation and good thermal stability
- Very low friction coefficient.

PACKAGING

- Available in white metal sprays of 500 ML.

ENVIRONMENT, HEALTH & SAFETY

Inflammable ! Do not expose at temperatures above 50°C.

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use has to be made in conformity with the local rules in force about used sprays disposal.

Throw away only if completely empty.

Keep out reach of children.

Propulsion gas (propane-butane) with no ozone depletion potential.

Shelf date: 3 years.

DEMOULSIL

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 15°C	kg/m ³	NFT 60101	720
Application temperature	°C	-	-20 à 150
Color	-	-	colorless

The average values are given for information only and ...