

KUTILUB ST

CUTTING OIL FOR TAPPING
AND SPRAY THREAD

500008/02.24

Rev. 5

DESCRIPTION & APPLICATIONS

KUTILUB ST is a fairly viscous, quasi-odorless tapping oil specially developed for the execution of threads and threads which are difficult in all types of steels, including high alloys and stainless steels.

KUTILUB ST is sprayed at short distance on the cutting tool before and during operation.

-

ADVANTAGES

- *

- KUTILUB ST makes it possible to obtain a remarkable surface finish and reduce the wear of taps and dies, thus increasing their life span.

PACKAGING

- Available in white metal sprays of 500 ML.
- Double ball valve for multi-position use.
- Delivered with 2 spray nozzles : 1 short and 1 long (100mm)

ENVIRONMENT, HEALTH & SAFETY

Inflammable ! Do not expose at temperatures above 50°C.

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use has to be made in conformity with the local rules in force about used sprays disposal.

Throw away only if completely empty.

Keep out reach of children.

Propulsion gas with no ozone depletion potential.

Shelf date: 3 years.

KUTILUB ST

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Density at 20°C	kg/m ³	NFT 60101	905
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	110
Color	-	-	yellow

The average values are given for information only and concern the active element.