

PROTECT ULTRA

WATER REPELLENT ANTICORROSION PROTECTION FLUID

500019/02.11

Rev. 0

DESCRIPTION & APPLICATIONS

PROTECT ULTRA is an outstanding anticorrosion fluid with excellent water repellent capabilities.

Small and medium size metal pieces can easily be protected against corrosion during manufacturing and storage of the finished products before shipment.

ADVANTAGES

- Gives a very resistant protection layer which remains resilient and does not stick.
- Powerful water repellent
- Does not dissolve varnish.
- Can easily be removed using white spirit.

PACKAGING

- Available in white metal sprays of 500 ML.
- Double ball valve for multi-position use.
- Delivered with 2 spray nozzles: 1 short and 1 long (100mm)

ENVIRONMENT, HEALTH & SAFETY

Inflammable! Do not expose at temperatures above 50°C.

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use has to be made in conformity with the local rules in force about used sprays disposal. Throw away only if completely empty.

Keep out reach of children.

Propulsion gas (propane-butane) with no ozone depletion potential.

Shelf date: 3 years.



PROTECT ULTRA

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Dry up time	min	-	env. 30
Protection indoors	month	-	8
Protection outdoors	month	-	5
Protection outdoors not sheltered	month	-	1/2
Corrosion test steel plate (20 days outdoors)	-	-	réussi
Corrosion test in humidity cabinet	day	DIN 51359	30
Salt spray test	day	DIN 50907	2

The average values are given for information only and ...