

# PTFE ULTRA

TEFLON<sup>®</sup> SPRAY

500020/05.17

Rev. 1

## **DESCRIPTION & APPLICATIONS**

PTFE ULTRA is a dispersion of colloidal particles of PTFE (polytetrafluoroethylene = TEFLON<sup>®</sup>) in a highly refined base oil.

PTFE ULTRA is recommended when long-term lubrication is desired, together with good resistance to high temperatures, excellent penetration and water repellent properties. PTFE ULTRA eliminates rust due to its dissolving characteristics.

PTFE ULTRA is also used for the lubrication and protection of bearings, roller bearings, joints, cables, chains, guidings, tools, fire weapons,

## **ADVANTAGES**

- Stable colloidal dispersion
- Economic use due to the long-term lubrication
- Lubrification at high temperatures
- Excellent penetration
- Corrosion inhibiting
- Releases bolts, screws and rusty materials

## **PACKAGING**

- Available in white metal sprays of 500 ML.

# PTFE ULTRA

## ENVIRONMENT, HEALTH & SAFETY

Inflammable ! Do not expose at temperatures above 50°C.

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use has to be made in conformity with the local rules in force about used sprays disposal.

Throw away only if completely empty.

Keep out reach of children.

Propulsion gas (propane-butane) with no ozone depletion potential.

Shelf date: 3 years.

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Specific gravity at 20°C	kg/m <sup>3</sup>	NFT 60101	807
Kinematic viscosity at 20°C	mm <sup>2</sup> /s (cSt)	NFT 60100	1
Flash point	°C	NFT 60118	-20
Pour point	°C	NFT 60105	-140

*The average values are given for information only and ...*