



CF WHITE OIL 68

Esca Food Grade, Food &
pharma

VASELINE

U510050

2/28/2025

V 25.2

Vaseline oil ISO-VG 68

DESCRIPTION

These oils are particularly recommended for the lubrication of materials for which a Codex oil is required in food industries : lubrication of mixing, slicing, wrapping, cutting machines, etc.

There are also recommended, strictly within pharmacopoeia, as component for cosmetic, pharmaceutical and phytosanitary industries : production of creams, ointments, lotions and aperients.

Plastic industries : plasticizing machine for objects destined to food contact.

ADVANTAGES

- Highly refined and free from unsaturated hydrocarbons
- Completely free from aromatic hydrocarbons.
- Color, odor and tasteless.
- White and fully transparent.

NORMS

/APPROVALS

CODEX

SPECIFICATIONS

RECOMMENDATIONS

Food & Pharma

AVAILABILITY

	Bulk	IBC	Barrel	60L/53kg	20L steel	20L/ 18 kg plastic	4X5L	12X1L Specials	small / 400 gr
U510050		/97	/68		/41	/29	/7		

CF WHITE OIL 68

TECHNICAL DATA

-----E510050

PROPERTIES	UNIT	METHOD	VALUE
ACEA	Association Constructeurs Européennes de l'Automobile		
API	American Petroleum institute		
SAE / ISO-VG / NLGI			68
COLOUR	Visual		WHITE
Density @ 15°C	kg / L	ASTM D1298	0.869
Pourpoint	°C	ASTM D97	-15
Flashpoint COC	°C	ASTM D92	224
Cinematic Viscosity @40°C	cSt	ASTM D7279	72
Kinematic viscosity @ 100°C	cSt	ASTM D7279	9.4
(V.I.) Viscosity index		ASTM D2270	
Copper Corrosion		ASTM D130	
Anilinepoint	°C	ASTM D611	
Noack evap	% w/w	ASTM D 5800	
Sulphated Ash	% weight		

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.