



GLASS CLEANER

Antifreeze, Windscreen washer

Chemical

U700009

9/2/2025

V 25.4

Ready to use windscreen washer fluid -20°C

DESCRIPTION

GLASS CLEANER is a ready to use windshield washer with anti-freeze properties, and is used in the windscreen washer systems of vehicles.

GLASS CLEANER defrosts and cleans the windows.

It is safe to use throughout the seasons.

ADVANTAGES

- Frost protection up to -20 °C
- Immediate action thanks to excellent wetting ability
- Great cleanliness of the windshield thanks to its detergency
- Protection of windshield washer systems (particularly at the nozzles) against scale
- Good compatibility with plastics and seals.

SPECIFICATIONS

ACEA: -, API: -,

NORMS / APPROVALS:

SPECIFICATIONS:

RECOMMENDATIONS: A clear view is a safety feature.

AVAILABILITY

| U700009 | Bulk | IBC | Barrel | 60L/53kg | 20L steel | 20L/ 18 kg plastic | 4X5L | 12X1L Specials | small / 400 gr |
|---------|------|-----|--------|----------|-----------|--------------------|------|----------------|----------------|
| | | | /68 | | | | /7 | | |



GLASS CLEANER

TECHNICAL DATA

E700009

| PROPERTIES | UNIT | METHOD | VALUE |
|------------------------------------|---|-------------|-----------|
| ACEA | Association Constructeurs Européennes de l'Automobile | | - |
| API | American Petroleum institute | | - |
| SAE / ISO-VG / NLGI | | | |
| COLOUR | Visual | | Blue |
| Density @ 15°C | kg / L | ASTM D1298 | 0.956 |
| Pourpoint | °C | ASTM D97 | -20 |
| Flashpoint COC | °C | ASTM D92 | 47 (PMCC) |
| Cinematic Viscosity @40°C | cSt | ASTM D7279 | |
| Kinematic viscosity @ 100°C | cSt | ASTM D7279 | |
| (V.I.) Viscosity index | | ASTM D2270 | |
| Copper Corrosion | | ASTM D130 | |
| Anilinepoint | °C | ASTM D611 | |
| Noack evap | % w/w | ASTM D 5800 | |
| | | | |
| Boiling point | | | > 75 |
| Sulphated Ash | % weight | | |
| | | | |
| | | | |

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.