



# ESCA FOOD GREASE

sprays, Dry Lubrication

White paraffine

L850018

5/28/2025

V 25.3

## Foodgrade Lubricant spray

### DESCRIPTION

ESCA FOOD GREASE is a colorless and odorless grease in a spray can that can be used as a lubricant or as a protective agent against corrosion.

FOOD GREASE is ideally suited for the food industry because it complies with the FDA standard 21 CFR 178.3570 (lubricants that come into incidental contact with food).

FOOD GREASE is a multifunctional grease with a temperature range from -20 to + 120 ° C. It makes the lubrication of bearings, slide bearings, chains, springs, hinges, cables, slides, various connections possible.

### ADVANTAGES

- Multifunctional and very wide range of applications.
- Degreases, cleans, lubricates and protects against and eliminates moisture.
- Excellent resistance to water and high pressures.
- Does not affect seals.

Thanks to its availability in aerosol can, FOOD GREASE allows the lubrication of hard-to-reach areas and components.

### NORMS/APPROVALS

**ACEA:** -, **API:** -, **APPROVAL:** 2Probiy Foodgrade H1 :, ESCA FOOD GREASE #GF1829333

### SPECIFICATIONS

NSF H1 approval: 163678

### RECOMMENDATIONS

Aluminium-complex, droppoint 240°C, Butane and propane gasses with no ozone depletion potential

### AVAILABILITY

|         | BULK | IBC | BARREL | 60L/53kg | 20L Steel | 20L Plastic | 4X5L | 12X1L | SMALL      |
|---------|------|-----|--------|----------|-----------|-------------|------|-------|------------|
| U500018 |      |     |        |          |           |             |      |       | 500MILnet. |





## ESCA FOOD GREASE

### TECHNICAL DATA

| PROPERTIES                  | UNIT                                                  | METHOD      | VALUE               |
|-----------------------------|-------------------------------------------------------|-------------|---------------------|
| ACEA                        | Association Constructeurs Européennes de l'Automobile |             | -                   |
| API                         | American Petroleum institute                          |             | -                   |
| COLOUR                      | Visual                                                |             | LIGHT YELLOW, BEIGE |
| Density @ 15°C              | kg / L                                                | ASTM D1298  |                     |
| Pourpoint                   | °C                                                    | ASTM D97    |                     |
| Flashpoint COC              | °C                                                    | ASTM D92    |                     |
| Cinematic Viscosity @40°C   | cSt                                                   | ASTM D7279  |                     |
| Kinematic viscosity @ 100°C | cSt                                                   | ASTM D7279  |                     |
| (V.I.) Viscosity index      |                                                       | ASTM D2270  |                     |
| Copper Corrosion            |                                                       | ASTM D130   |                     |
| sollulable in water         |                                                       |             | none                |
| Noack evap                  | % w/w                                                 | ASTM D 5800 |                     |
|                             |                                                       |             |                     |
| Sulphated Ash               | % weight                                              |             |                     |
|                             |                                                       |             |                     |
|                             |                                                       |             |                     |

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened. Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.