



MARINE SAE 30

HDMO, 4-T

MINERAL

U110049

9/2/2025

V 25.4

Monograde oil for marine engines

DESCRIPTION

MARINE SAE 30 was specially developed for the lubrication of heavily loaded marine engines.

These engines are used in all possible applications from pumping to off-roading.

Marine SAE 30 is perfectly applicable for engines that have to operate and run on heavy diesel fuel with a high sulfur content.

ADVANTAGES

- High detergent and dispersant properties.
- Excellent protection against rust and corrosion.
- Very good anti-wear properties.

SPECIFICATIONS

ACEA: -, **API:** CF-4,

NORMS / APPROVALS: SAE J300

SPECIFICATIONS: MIL-L-2104E, Wartsila 4T, Baudoin Engines

RECOMMENDATIONS: Agricultural & construction machines engine +hydraulic

AVAILABILITY

U110049	Bulk	IBC	Barrel	60L/53kg	20L steel	20L/ 18 kg plastic	4X5L	12X1L Specials	small / 400 gr
	/99	/97	/68	/42	/41	/29	/7	/12	

MARINE SAE 30

TECHNICAL DATA

-----E110049

PROPERTIES	UNIT	METHOD	VALUE
ACEA	Association Constructeurs Européennes de l'Automobile		-
API	American Petroleum institute		CF-4
SAE / ISO-VG / NLGI			30
COLOUR	Visual		
Density @ 15°C	kg / L	ASTM D1298	0.899
Pourpoint	°C	ASTM D97	-24
Flashpoint COC	°C	ASTM D92	230
Cinematic Viscosity @40°C	cSt	ASTM D7279	105
Kinematic viscosity @ 100°C	cSt	ASTM D7279	11.8
(V.I.) Viscosity index		ASTM D2270	100
Copper Corrosion		ASTM D130	
Anilinepoint	°C	ASTM D611	
Noack evap	% w/w	ASTM D 5800	
TBN	mg KOH/g	ASTM D 2896B	3000%
Sulphated Ash	% weight		3.75

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.