



Opaljet Hybrid 0W20

PCMO, High Tech

SYNTHETIC

U120025

5/23/2024

Rev 2

High technology ACEA C5 / A7 / B7 engine oil with LSPI protection SAE 0W20

DESCRIPTION

Contemporary hybrid engines are very diverse in design.

OPALJET HYBRID 0W20 is a balanced formula to peak at those diverse needs due to exceptional quality base oils and additives

The things in common are the need for:

- A lasting lubricant film,
- A great fluidity to ensure allround lubrication.
- Top Class compression protection.

ADVANTAGES

- Fuel economy.
- A high and very stable viscosity index.
- A great resistance to "shearing".
- A very smooth cold start.
- A very strong resistance to oxidation.
- A safe lubricating film at very high operating temperatures

NORMS/APPROVALS

ACEA C5-16, A7/B7 - API SP, SP Resource Conserving -

SPECIFICATIONS

ILSAC GF-6A, BMW LongLife 17 FE+, Fiat 9.55535-GSX, Ford WSS M2C 947-B1, Ford WSS M2C 962-A1, Honda Hybrid, Jaguar STJLR.03.5006, Lexus Hybrid, MB 229.71, MB 229.72, Renault E-tech, Toyota Hybrid

RECOMMENDATIONS

First choice for durability in hybrid engines

AVAILABILITY

U120025	Bulk	IBC	Gr. Vat	60L/53kg	20L steel	20L plastic	4X5L	12X1L	Klein
	/99	/97	/68	/42	/41	/29	/7	/12	

Opaljet Hybrid 0W20

TECHNICAL DATA

PROPERTIES	UNIT	METHOD	VALUE
ACEA	Association Constructeurs Européennes de l'Automobile		C5-16, A7/B7
API	American Petroleum institute		SP, SP Resource Conserving
COLOUR	Visual		
Density @ 15°C	kg / L	ASTM D1298	0
Pourpoint	°C	ASTM D97	-51
Flashpoint COC	°C	ASTM D92	222
Cinematic Viscosity @40°C	cSt	ASTM D7279	42
Kinematic viscosity @ 100°C	cSt	ASTM D7279	8.3
(V.I.) Viscosity index		ASTM D2270	179
Copper Corrosion		ASTM D130	
Anilinepoint	°C	ASTM D611	
Noack evap	% w/w	ASTM D 5800	
TBN	mg KoH/g	ASTM D 2896B	7.8
Sulphated Ash	% weight		0.77

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.