

MEGARA RD 20W50

LUBRICANT GASOLINE AND DIESEL ENGINES
WITH OR WITHOUT TURBO

120034/12.18

Rev. 2

DESCRIPTION & APPLICATIONS

MEGARA RD is recommended for the lubrication of diesel and gasoline engines, and for some POWERSHIFT transmissions. Also suitable for oldtimer lubrication.

ADVANTAGES

- Anti-wear protection
- Resistance to oxidation
- Anti-corrosion protection
- High temperature stability, allowing usage under very hard conditions
Protects against sludge

PERFORMANCES

Satisfies to the following specifications:

ACEA A2-96 Issue 3 (2002)

ACEA B3-98 Issue 2 (2004)

ACEA E2-96 Issue 5 (2007)

ALLISON C4

API CE/CF4/SG

MB 227.1

Volvo VDS

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

MEGARA RD 20W50

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	20W50
Specific gravity at 15°C	kg/m ³	NFT 60101	875
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	181
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	19,4
Viscosity index	-	NFT 60136	123
Dynamic viscosity at -10°C	mPa.s	ASTM D2602	3750
Flash point	°C	NFT 60118	239
Pour point	°C	NFT 60105	-27
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	4,9

The average values are given for information only.