



# AGRIALLE 15W40

HDMO, STOU

MINERAL

U120035

9/2/2025

V 25.4

## Mineral STOU ( engine+transmission) oil SAE 15W-40

### DESCRIPTION

Agrialle 15W40 is a multipurpose lubricant for farm tractors. It is a S.T.O.U. (Super Tractor Oil Universal) for optimal lubrication of all parts of agricultural equipment: tractors, harvesters, shredders, etc.

All engines, hydraulic systems, mechanical transmissions, wet brakes can be lubricated with Agrialle.

The high-quality base oils and specific additives ensure good corrosion resistance, good anti-foam properties and good shear-resistance.

### ADVANTAGES

- All-round applicable where a S.T.O.U. 15W40 is required.
- Ideal for mixed fleets.
- Ideal to rationalise your oil inventory.
- Perfectly applicable for heavy loads of mechanical transmissions.
- Good for preventing brake noises.
- The perfect motor oil when the OEM-homologation Massey Ferguson M1144 is required.

### SPECIFICATIONS

**ACEA:** E4-08, E7-08, **API:** CE, CF-4, CG-4, CI-4, GL4, GL5,

**NORMS / APPROVALS:** John Deere J20C, John Deere J20D, John Deere J27

**SPECIFICATIONS:** Allison C4, CAT TO-4, MB 227.1, MB 228.1, MB 228.3 /DTFR 15B110, Massey Ferguson M1139, Massey Ferguson M1141, Massey Ferguson M1144, Massey Ferguson M1145, Mil-L-2104D, ZF-TE-ML 06B, ZF-TE-ML 06C, ZF-TE-ML 07B, Ford WSS M2C 159-B

**RECOMMENDATIONS:** Tractors and other vehicles requiring STOU-capacities

### AVAILABILITY

|         | Bulk | IBC | Barrel | 60L/53kg | 20L steel | 20L/ 18 kg plastic | 4X5L | 12X1L Specials | small / 400 gr |
|---------|------|-----|--------|----------|-----------|--------------------|------|----------------|----------------|
| U120035 | /99  | /97 | /68    | /42      | /41       | /29                | /7   | /12            |                |

# AGRIALLE 15W40

## TECHNICAL DATA

-----E120035

| PROPERTIES                         | UNIT                                                  | METHOD       | VALUE                          |
|------------------------------------|-------------------------------------------------------|--------------|--------------------------------|
| <b>ACEA</b>                        | Association Constructeurs Européennes de l'Automobile |              | E4-08, E7-08                   |
| <b>API</b>                         | American Petroleum institute                          |              | CE, CF-4, CG-4, CI-4, GL4, GL5 |
| <b>SAE / ISO-VG / NLGI</b>         |                                                       |              | 15W-40                         |
| <b>COLOUR</b>                      | Visual                                                |              |                                |
| <b>Density @ 15°C</b>              | kg / L                                                | ASTM D1298   | 0.890                          |
| <b>Pourpoint</b>                   | °C                                                    | ASTM D97     | -33                            |
| <b>Flashpoint COC</b>              | °C                                                    | ASTM D92     | 240                            |
| <b>Cinematic Viscosity @40°C</b>   | cSt                                                   | ASTM D7279   | 104                            |
| <b>Kinematic viscosity @ 100°C</b> | cSt                                                   | ASTM D7279   | 14.1                           |
| <b>(V.I.) Viscosity index</b>      |                                                       | ASTM D2270   | 138                            |
| <b>Copper Corrosion</b>            |                                                       | ASTM D130    |                                |
| <b>Anilinepoint</b>                | °C                                                    | ASTM D611    |                                |
| <b>Noack evap</b>                  | % w/w                                                 | ASTM D 5800  |                                |
| <b>CCS ( cold crank )</b>          | cP @ -20°C                                            | ASTM D 5293  | 6705                           |
| <b>TBN</b>                         | mg KOH/g                                              | ASTM D 2896B | 12.7                           |
| <b>Sulphated Ash</b>               | % weight                                              |              | 1.55                           |
|                                    |                                                       |              |                                |
|                                    |                                                       |              |                                |

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.