



# AGRIALLE 10W30

HDMO, STOU

MINERAL

U120072

9/2/2025

V 25.4

## Mineral STOU ( engine+transmission) oil SAE 10W-30

### DESCRIPTION

AGRIALLE, a STOU (Super Tractor Oil Universal) lubricant, is used for the lubrication of any mechanism of agricultural machines : tractors, combine harvesters.

This multifunctional lubricant is recommended because it allows the user to rationalize of supply and therefore prevents against any risk of error.

### ADVANTAGES

- Multifunctional : engines, hydraulic, mechanical transmissions, wet brakes.
- Viscosity has been studied for an easy start at low temperatures and for a quick transmission of hydraulic control.
- Well-adapted to load which can be found on mechanical transmissions of these machines.

### SPECIFICATIONS

**ACEA:** E4-08, E7-08, **API:** CE, CF-4, CI-4, GL4, GL5, SF,

**NORMS / APPROVALS:** John Deere J20C, John Deere J20D, John Deere J27

**SPECIFICATIONS:** Allison C4, CAT TO-4, Ford WSS M2C 159-B, John Deere J20A, John Deere J20B, MAN 271, MB 227.1, MB 228.1, MB 228.3 /DTFR 15B110, Massey Ferguson M1139, Massey Ferguson M1141, Massey Ferguson M1144, Massey Ferguson M1145, Vickers M2950S, ZF-TE-ML 06B, ZF-TE

**RECOMMENDATIONS:** Tractors and other vehicles requiring STOU-capacities

### AVAILABILITY

	Bulk	IBC	Barrel	60L/53kg	20L steel	20L/ 18 kg plastic	4X5L	12X1L Specials	small / 400 gr
U120072	/99	/97	/68	/42	/41	/29	/7	/12	

# AGRIALLE 10W30

## TECHNICAL DATA

-----E120072

PROPERTIES	UNIT	METHOD	VALUE
<b>ACEA</b>	Association Constructeurs Européennes de l'Automobile		E4-08, E7-08
<b>API</b>	American Petroleum institute		CE, CF-4, CI-4, GL4, GL5, SF
<b>SAE / ISO-VG / NLGI</b>			10W-30
<b>COLOUR</b>	Visual		
<b>Density @ 15°C</b>	kg / L	ASTM D1298	0.890
<b>Pourpoint</b>	°C	ASTM D97	-36
<b>Flashpoint COC</b>	°C	ASTM D92	234
<b>Cinematic Viscosity @40°C</b>	cSt	ASTM D7279	64
<b>Kinematic viscosity @ 100°C</b>	cSt	ASTM D7279	10.2
<b>(V.I.) Viscosity index</b>		ASTM D2270	148
<b>Copper Corrosion</b>		ASTM D130	
<b>Anilinepoint</b>	°C	ASTM D611	
<b>Noack evap</b>	% w/w	ASTM D 5800	
<b>CCS ( cold crank )</b>	cP @ -25°C	ASTM D 5293	5258
<b>TBN</b>	mg KOH/g	ASTM D 2896B	12.6
<b>Sulphated Ash</b>	% weight		1.47

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.