



Matic DX III

Transmission, ATF

MINERAL

U210038

1/30/2025

V 25.1

ATF Fluid designed to the Dexron III-G standard.

DESCRIPTION

Matic DX III is an ATF (Automatic Transmission Fluid), Dexron III-G.

This mineral based oil contains additives to provide excellent friction properties, a strong anti-oxidative ability (against cooler-corrosion), a perfect fluidity at very low temperatures and an unchanged behavior and quality at high temperatures.

Made to match and supersede the Dexron III specifications the product has a wide range of applications, often referred to as a power-assisted steering fluid.

ADVANTAGES

- The ideal ATF where DEXRON III is required.
- Perfectly compatible with seals, ferrous and non-ferrous metals.
- Can also be used as hydraulic fluid, type HV, viscosity ISO VG 32.

NORMS

/APPROVALS

Dexron III-GVoith Turbo H55.6335, ZF TE-ML 04D, ZF TE-ML 14A

SPECIFICATIONS

Allison C4, BMW DEXRON III, Ford Mercon C(CFT30), DAF TORQUE CONVERTER, Hyundai SP III, MAN 339 tpe L-1, MAN 339 type V1, MAN 339 type Z1, MAN 339 type Z2, Mazda ATF F-1, MB 236.1 / DTFR 13a100, MB 236.5, MB 236.6 , MB 236.7 / DTFR 13C140, MB 236.9 / DTFR

RECOMMENDATIONS

BMW ATF-4, Chrysler / Dodge / Jeep +/+2 / +3, Voith Diwa 5/6, Voith DIWA D85 / D86, Volvo 97301, Volvo 97330, Volvo 97341, Allison TES-389

AVAILABILITY

	Bulk	IBC	Barrel	60L/53kg	20L steel	20L/ 18 kg plastic	4X5L	12X1L Specials	small / 400 gr
U210038	/99	/97	/68	/42	/41	/29	/7	/12	

Matic DX III

TECHNICAL DATA

-----E210038

PROPERTIES	UNIT	METHOD	VALUE
ACEA	Association Constructeurs Européennes de l'Automobile		
API	American Petroleum institute		Dexron III-G
SAE / ISO-VG / NLGI			35.8
COLOUR	Visual		RED
Density @ 15°C	kg / L	ASTM D1298	0.862
Pourpoint	°C	ASTM D97	-48
Flashpoint COC	°C	ASTM D92	176
Cinematic Viscosity @40°C	cSt	ASTM D7279	35.8
Kinematic viscosity @ 100°C	cSt	ASTM D7279	8
(V.I.) Viscosity index		ASTM D2270	200
Copper Corrosion		ASTM D130	
Anilinepoint	°C	ASTM D611	
Noack evap	% w/w	ASTM D 5800	
Sulphated Ash	% weight		

For guidelines on emergencies, handling and storage etc., please refer to the SDS/MSDS. This is available on request. Storage of the product: 3 years in a sheltered environment, unopened.

Any handling/disposal/liquidation of the product must comply with local regulations for petrochemicals. Advice will be given on request.