

Gerion Drive 75W90

100% SYNTHETIC LUBRICANT FOR GEARBOXES AND REAR AXLES.

210073/06.24

Rev. 9

DESCRIPTION & APPLICATIONS

Gerion Drive is a 100% synthetic oil suitable for the lubrication of mechanical gearboxes and rear axles where a performance level API GL4 or GL5 is required, with extreme pressure (EP) and anti-wear properties.

Gerion Drive ensures a constant viscosity and can be used for extended drain intervals because the high-quality synthetic base oils and specific additives that are used.

ADVANTAGES

- Allround applicable where API GL-4 or GL-5 is required with extended drain intervals.
- Perfect for the proper protection of synchros in bronze or molybdenum.
- Suitable for standardizing the lubricant stock.

PERFORMANCES

Satisfies to the following specifications:

API GL4/GL5/MT-1

DAF

IVECO

MIL-L-2105D

MIL-L-2105E

MACK GO-J

MAN 341 Type Z-2

MAN 342 M-3

MB 235,11 / DTFR 13B110

SAE J2360

SCANIA STO:01

Volvo 97312

ZF-TE ML 02B/05A/07A/12L/12N/16B/16F/17B/19C/21A

Gerion Drive 75W90

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	75W90
Density at 15 °C	kg/l	ASTM D4052	869
Kinematic viscosity at 100°C	mm²/s.	ASTM D445	84
Kinematic viscosity at 100°C	mm²/s.	ASTM D7279	15
Viscosity index	-	ASTM D2270	195
Flash point (COC)	°C	ASTM D 92	184
Pour point	°C	ASTM D7346	-45

The average values are given for information only.