

Gerion Drive 75W140

100 % SYNTHETIC LUBRICANT FOR GEARBOXES AND FINAL DRIVES

210074/11.16

Rev. 2

DESCRIPTION & APPLICATIONS

GERION DRIVE 75W140 is a lubricant specifically designed to lubricate the gearboxes and final drives of all private and industrial vehicles.

GERION DRIVE 75W140 is specially recommended to lubricate self-locking or limited slip differentials fitted to industrial and off-road vehicles (4x4).

ADVANTAGES

- 100 % synthetic for exceptional product longevity
- Extreme-Pressure performance and reinforced anti-wear properties for effective resistance at very high loads.
- High viscosity index with excellent shear resistance

PERFORMANCES

Satisfies to the following specifications:

API GL4/GL5/MT-1

MIL-L-2105D

MIL-PRF-2105 E

SAE J2360

SCANIA STO:01

ZF-TE ML 05A/07A/12N/16F/19C/21A

ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal.

When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

Gerion Drive 75W140

PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	75W140
Specific gravity at 15°C	kg/m ³	NFT 60101	876
Kinematic viscosity at 40°C	mm ² /s (cSt)	NFT 60100	188
Kinematic viscosity at 100°C	mm ² /s (cSt)	NFT 60100	25,8
Viscosity index	-	NFT 60136	171
Flash point (COC)	°C	ASTM D 92	252
Pour point	°C	NFT 60105	-48

The average values are given for information only.