

# Agrialle SAE 15W30

Multifunctional 15W30 lubricant (STOU) for agriculture

263530/09.17

Rev. 1

## DESCRIPTION & APPLICATIONS

Agrialle 15W30 is a multipurpose lubricant for farm tractors. It is a S.T.O.U. (Super Tractor Oil Universal) for optimum lubrication of all parts of agricultural equipment: tractors, harvesters, shredders, etc. Engines, hydraulic systems, mechanical transmissions and wet brake systems can be lubricated with Agrialle. The quality base oils and specific additivation ensure good corrosion resistance, good anti-foam properties and good resistance to shearing. Your machine is always optimally lubricated. Agrialle is an ideal partner for the rationalization of your oil stock, prevents the use of an incorrect lubricant and enables you to limit your stock to a minimum.

## ADVANTAGES

- Allround applicable where a S.T.O.U. 15W30 is required.
  - Ideal for mixed fleets.
  - Ideal to simplify your oil stock.
- Perfectly suited for heavy loads of mechanical transmissions.
- Good for preventing brake noise.

## PERFORMANCES

Satisfies to the following specifications:

ACEA E4-08/E7

ALLISON C4

API CI-4/GL4

API GL5 (low speed, high torque)

CAT TO2

Ford M2C 159B

JD J20A/J20C/J27A

MF M1139/M1141/M1144/M1145

New Holland 82009202

NH 410B

ZF-TE-ML 06B/06C/07B

# Agrialle SAE 15W30

## ENVIRONMENT, HEALTH & SAFETY

Please consult also the Safety Data Sheet about how to manipulate and to stock the product as well as to learn about the first aid measurements in case of accident.

Elimination after use must be made in conformity with the local rules in force about used oils disposal. When needed, Safety Data Sheet can be obtained upon request.

Conservation of the product: 3 year(s) in closed container and sheltered.

## PROPERTIES

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
SAE grade	-	-	15W30
Specific gravity at 15°C	kg/m <sup>3</sup>	NFT 60101	890
Kinematic viscosity at 40°C	mm <sup>2</sup> /s (cSt)	NFT 60100	79,4
Kinematic viscosity at 100°C	mm <sup>2</sup> /s (cSt)	NFT 60100	10,9
Viscosity index	-	NFT 60136	125
Viscosity CCS at -20°C	mPa.s	NFT 60152	6031
Flash point	°C	ISO 2719	234
Pour point	°C	NFT 60105	-33
Sulphated ash content	% wheight	NF T 60143	1,5
TBN (Total Base Number)	mg KOH/g	ASTM D 2896	12,7

*The average values are given for information only.*